

XF Waist Level Finder Diopters

We are pleased to announce availability of the Waist Level Finder Diopter lenses.

The XF Waist Level Finder Diopters are easy to exchange by the user when using the included tool.



Choosing the correct Diopter lens

We recommend that partners purchase the full kit of four diopters (-1/-2/+1/+2) in order to let the customer try out the different options before buying.

It might be difficult to judge exactly which diopter will best suit the photographer's eyesight based solely on the strength of the glasses (or contact lenses) being used. Therefore, we recommend testing the diopter on the camera in an actual working situation to make sure that optimal optical correction is achieved under all conditions.

Part numbers and pricing:

- 73094 XF Waist Level Finder Diopter +2
- 73095 XF Waist Level Finder Diopter +1
- 73096 XF Waist Level Finder Diopter 0 (Included with the WLF)
- 73097 XF Waist Level Finder Diopter -1
- 73099 XF Waist Level Finder Diopter -2

Each Waist Level Finder Diopter will be supplied in a small optical protective box and a Schneider Kreuznach soft pouch.

Price for 1 unit is € 199/\$229.



Removing the Waist Level Finder Diopter

First, remove the Waist Level Finder from the XF Camera. Then open the finder by lifting the top plate to its vertical position and unlock the built-in magnifier by sliding the silver latch upwards.

Position the included tool inside of the Waist Level Finder and make sure that the two tabs on the tool align with the two notches in the Diopter frame.

Turn the tool slightly counter-clockwise to unlock the Diopter from the top frame. Then continue to turn counter-clockwise until the Diopter is fully released and remove it with your fingertips from the top of the Waist Level Finder.



Mounting the new Diopter

To mount the new Diopter, place it in the frame on the top of the Waist Level Finder and make sure that the white dot is facing towards the back side of the finder.

Turn the Diopter clockwise with your fingertips until its frame is fastened in the flange.

Position the included tool inside of the Waist Level Finder and make sure that the two tabs on the tool align with the two notches in the Diopter frame.

Turn the tool clockwise until the Diopter is fully locked into position.

Use the supplied cloth to clean the Diopter for any fingerprints and dust.

