

High-productivity metric camera

# Phase One iXM series



PHASE**ONE**



# iXM series

Phase One iXM cameras are designed for the most demanding mapping, inspection, space and security applications.

All iXM cameras are medium format cameras, based on CMOS sensor, and purpose-built for an easy integration into the most demanding camera systems.



## Wide coverage

The widest possible coverage with high resolution and pixel count to capture incredible details of very large areas.



## High dynamic range

The high dynamic range to capture exceptional details even in the most challenging light conditions boosting productivity.



## Innovative shutter technology

The iXM family provides the most advanced shutter options on the market. The RS Shutters allow for an unbeatable shutter speed rate of 1/2500. To push the limit even further, an electronic global shutter option is also available to reach the fastest shutter speed rate on the market of 1/16.000.



## Build for seamless integration

The iXM's compact size and low weight facilitates effortless integration. By connecting the iXM to GNSS receiver and IMU, precise geolocation of the images are ensured. Plus, taking full control of the camera settings has never been so easy with our comprehensive Software Development Kit.



# Flexible configurations to boost productivity

The iXM family offers flexible configurations to cover a wide range of resolutions to suit your specific need and application from 100 MP all the way up to 280 MP, with both NIR and RGB options.

A wide range of compatible lenses let you choose the optimal lens for your specific mission and operating conditions. Whether you are engaged in aerial mapping,

surveying, environmental monitoring, or infrastructure inspection, Phase One iXM cameras set the highest possible standard for image quality, productivity, and accuracy.

Elevate your imaging capabilities with the iXM camera family and capture the world from above with unparalleled precision and detail.

iXM-100



iXM-GS120



iXM-RS150F



iXM-RS280F









Camera comparisons



	iXM-100	iXM-GS120	iXM-RS150F	iXM-280F
SPECIFICATIONS	Resolution			
	100 MP	120 MP	150 MP	284 MP
	11,664 x 8,750	12,768 x 9,564	14,204 x 10,652	20,150 x 14,118
	Color options			
	RGB & Achromatic	RGB & Achromatic	RGB & Achromatic	RGB
	Dynamic range (dB)			
	83	80	83	83
	Pixel size (µm)			
	3.76	3.45	3.76	3.76
	Light sensitivity (ISO)			
	RGB: 50-6400 ACH: 200-25600	RGB: 200-6400 ACH: 800-25600	RGB: 50-6400 ACH: 200-25600	RGB: 50-6400
	Max shutter speed (sec)			
	1/2500	1/16000	1/2500 or 1/2000 depending on lens	1/2000
INTERFACE	Camera type			
	Medium format	Medium format	Medium format	Large format
	Continuous frame rate (fps)			
	3	6	2	2
	RAW file compression (approx.) (IIQ)			
	65 MB	95 MB	100 MB	2 x 100 MB
	Lens mount			
	Phase One RSM	Phase One RSM and RS	Phase One RS	Phase One RS (90mm only)
	Image data			
	USB 3.0, Ethernet 10 G (Fiber/Copper)	USB 3.0, Ethernet 10 G (Fiber/Copper)	USB 3.0, Ethernet 10 G (Fiber/Copper)	USB 3.0, Ethernet 10 G (Fiber/Copper)
POWER	H/W signals			
	Inputs: Trigger, Black reference	Inputs: Trigger, Black reference	Inputs: Trigger, Black reference	Inputs: Trigger, Black reference
	Outputs: Camera ready, MEP	Outputs: Camera ready, MEP	Outputs: Camera ready, MEP	Outputs: Camera ready, MEP
	HDMI			
MECHANICAL	Weight (g)			
	630 (excluding lens)	630 (excluding lens)	1000 (excluding lens)	4700 (incl. lenses)
OPERATING CONDITIONS	Temperature (°)			
	- 10 to 40	- 10 to 40	- 10 to 40	- 10 to 40
4-BAND CONFIGURATION	Humidity (%) (non condensing)			
	15 to 80	15 to 80	15 to 80	15 to 80
4-BAND CONFIGURATION	Synchronization speed in multiple camera configuration (µsec)			
	50	50	50	50
POWER	Max. power consumption (W)			
	16	20	16	32
MECHANICAL	Power input (VDC)			
	12 - 30	12 - 30	12 - 30	12 - 30
OPERATING CONDITIONS	Temperature (°)			
	- 10 to 40	- 10 to 40	- 10 to 40	- 10 to 40
4-BAND CONFIGURATION	Humidity (%) (non condensing)			
	15 to 80	15 to 80	15 to 80	15 to 80
4-BAND CONFIGURATION	Synchronization speed in multiple camera configuration (µsec)			
	50	50	50	50
POWER	Max. power consumption (W)			
	16	20	16	32
MECHANICAL	Power input (VDC)			
	12 - 30	12 - 30	12 - 30	12 - 30
OPERATING CONDITIONS	Temperature (°)			
	- 10 to 40	- 10 to 40	- 10 to 40	- 10 to 40
4-BAND CONFIGURATION	Humidity (%) (non condensing)			
	15 to 80	15 to 80	15 to 80	15 to 80
4-BAND CONFIGURATION	Synchronization speed in multiple camera configuration (µsec)			
	50	50	50	50
POWER	Max. power consumption (W)			
	16	20	16	32
MECHANICAL	Power input (VDC)			
	12 - 30	12 - 30	12 - 30	12 - 30
OPERATING CONDITIONS	Temperature (°)			
	- 10 to 40	- 10 to 40	- 10 to 40	- 10 to 40
4-BAND CONFIGURATION	Humidity (%) (non condensing)			
	15 to 80	15 to 80	15 to 80	15 to 80
4-BAND CONFIGURATION	Synchronization speed in multiple camera configuration (µsec)			
	50	50	50	50
POWER	Max. power consumption (W)			
	16	20	16	32
MECHANICAL	Power input (VDC)			
	12 - 30	12 - 30	12 - 30	12 - 30
OPERATING CONDITIONS	Temperature (°)			
	- 10 to 40	- 10 to 40	- 10 to 40	- 10 to 40
4-BAND CONFIGURATION	Humidity (%) (non condensing)			
	15 to 80	15 to 80	15 to 80	15 to 80
4-BAND CONFIGURATION	Synchronization speed in multiple camera configuration (µsec)			
	50	50	50	50
POWER	Max. power consumption (W)			
	16	20	16	32
MECHANICAL	Power input (VDC)			
	12 - 30	12 - 30	12 - 30	12 - 30
OPERATING CONDITIONS	Temperature (°)			
	- 10 to 40	- 10 to 40	- 10 to 40	- 10 to 40
4-BAND CONFIGURATION	Humidity (%) (non condensing)			
	15 to 80	15 to 80	15 to 80	15 to 80
4-BAND CONFIGURATION	Synchronization speed in multiple camera configuration (µsec)			
	50	50	50	50
POWER	Max. power consumption (W)			
	16	20	16	32
MECHANICAL	Power input (VDC)			
	12 - 30	12 - 30	12 - 30	12 - 30
OPERATING CONDITIONS	Temperature (°)			
	- 10 to 40	- 10 to 40	- 10 to 40	- 10 to 40
4-BAND CONFIGURATION	Humidity (%) (non condensing)			
	15 to 80	15 to 80	15 to 80	15 to 80
4-BAND CONFIGURATION	Synchronization speed in multiple camera configuration (µsec)			
	50	50	50	50
POWER	Max. power consumption (W)			
	16	20	16	32
MECHANICAL	Power input (VDC)			
	12 - 30	12 - 30	12 - 30	12 - 30
OPERATING CONDITIONS	Temperature (°)			
	- 10 to 40	- 10 to 40	- 10 to 40	- 10 to 40
4-BAND CONFIGURATION	Humidity (%) (non condensing)			
	15 to 80	15 to 80	15 to 80	15 to 80
4-BAND CONFIGURATION	Synchronization speed in multiple camera configuration (µsec)			
	50	50	50	50
POWER	Max. power consumption (W)			
	16	20	16	32
MECHANICAL	Power input (VDC)			
	12 - 30	12 - 30	12 - 30	12 - 30
OPERATING CONDITIONS	Temperature (°)			
	- 10 to 40	- 10 to 40	- 10 to 40	- 10 to 40
4-BAND CONFIGURATION	Humidity (%) (non condensing)			
	15 to 80	15 to 80	15 to 80	15 to 80
4-BAND CONFIGURATION	Synchronization speed in multiple camera configuration (µsec)			
	50	50	50	50
POWER	Max. power consumption (W)			
	16	20	16	32
MECHANICAL	Power input (VDC)			
	12 - 30	12 - 30	12 - 30	12 - 30
OPERATING CONDITIONS	Temperature (°)			
	- 10 to 40	- 10 to 40	- 10 to 40	- 10 to 40
4-BAND CONFIGURATION	Humidity (%) (non condensing)			
	15 to 80	15 to 80	15 to 80	15 to 80
4-BAND CONFIGURATION	Synchronization speed in multiple camera configuration (µsec)			
	50	50	50	50
POWER	Max. power consumption (W)			
	16	20	16	32
MECHANICAL	Power input (VDC)			
	12 - 30	12 - 30	12 - 30	12 - 30
OPERATING CONDITIONS	Temperature (°)			
	- 10 to 40	- 10 to 40	- 10 to 40	- 10 to 40
4-BAND CONFIGURATION	Humidity (%) (non condensing)			
	15 to 80	15 to 80	15 to 80	15 to 80
4-BAND CONFIGURATION	Synchronization speed in multiple camera configuration (µsec)			
	50	50	50	50
POWER	Max. power consumption (W)			
	16	20	16	32
MECHANICAL	Power input (VDC)			
	12 - 30	12 - 30	12 - 30	12 - 30
OPERATING CONDITIONS	Temperature (°)			
	- 10 to 40	- 10 to 40	- 10 to 40	- 10 to 40
4-BAND CONFIGURATION	Humidity (%) (non condensing)			
	15 to 80	15 to 80	15 to 80	15 to 80
4-BAND CONFIGURATION	Synchronization speed in multiple camera configuration (µsec)			
	50	50	50	50
POWER	Max. power consumption (W)			
	16	20	16	32
MECHANICAL	Power input (VDC)			
	12 - 30	12 - 30	12 - 30	12 - 30
OPERATING CONDITIONS	Temperature (°)			
	- 10 to 40	- 10 to 40	- 10 to 40	- 10 to 40
4-BAND CONFIGURATION	Humidity (%) (non condensing)			
	15 to 80	15 to 80	15 to 80	15 to 80
4-BAND CONFIGURATION	Synchronization speed in multiple camera configuration (µsec)			
	50	50	50	50
POWER	Max. power consumption (W)			
	16	20	16	32
MECHANICAL	Power input (VDC)			
	12 - 30	12 - 30	12 - 30	12 - 30
OPERATING CONDITIONS	Temperature (°)			
	- 10 to 40	- 10 to 40	- 10 to 40	- 10 to 40
4-BAND CONFIGURATION	Humidity (%) (non condensing)			
	15 to 80	15 to 80	15 to 80	15 to 80
4-BAND CONFIGURATION	Synchronization speed in multiple camera configuration (µsec)			
	50	50	50	50
POWER	Max. power consumption (W)			
	16	20	16	32
MECHANICAL	Power input (VDC)			
	12 - 30	12 - 30	12 - 30	12 - 30
OPERATING CONDITIONS	Temperature (°)			
	- 10 to 40	- 10 to 40	- 10 to 40	- 10 to 40
4-BAND CONFIGURATION	Humidity (%) (non condensing)			
	15 to 80	15 to 80	15 to 80	15 to 80
4-BAND CONFIGURATION	Synchronization speed in multiple camera configuration (µsec)			
	50	50	50	50
POWER	Max. power consumption (W)			
	16	20	16	32
MECHANICAL	Power input (VDC)			
	12 - 30	12 - 30	12 - 30	12 - 30
OPERATING CONDITIONS	Temperature (°)			
	- 10 to 40	- 10 to 40	- 10 to 40	- 10 to 40
4-BAND CONFIGURATION	Humidity (%) (non condensing)			
	15 to 80	15 to 80	15 to 80	15 to 80
4-BAND CONFIGURATION	Synchronization speed in multiple camera configuration (µsec)			
	50	50	50	50
POWER	Max. power consumption (W)			
	16	20	16	32
MECHANICAL	Power input (VDC)			
	12 - 30	12 - 30	12 - 30	12 - 30
OPERATING CONDITIONS	Temperature (°)			
	- 10 to 40	- 10 to 40	- 10 to 40	- 10 to 40
4-BAND CONFIGURATION	Humidity (%) (non condensing)			
	15 to 80	15 to 80	15 to 80	15 to 80
4-BAND CONFIGURATION	Synchronization speed in multiple camera configuration (µsec)			
	50	50	50	50
POWER	Max. power consumption (W)			
	16	20	16	32
MECHANICAL	Power input (VDC)			
	12 - 30	12 - 30	12 - 30	12 - 30
OPERATING CONDITIONS	Temperature (°)			
	- 10 to 40	- 10 to 40	- 10 to 40	- 10 to 40
4-BAND CONFIGURATION	Humidity (%) (non condensing)			
	15 to 80	15 to 80	15 to 80	15 to 80
4-BAND CONFIGURATION	Synchronization speed in multiple camera configuration (µsec)			
	50	50	50	50
POWER	Max. power consumption (W)			
	16	20	16	32



## About Phase One

Phase One A/S is a leading researcher, developer and manufacturer of medium-and large-format digital cameras and imaging systems. Phase One has pioneered the development of digital photography technology since 1994. The company has developed core imaging technologies and a range of digital cameras and imaging modules, providing the world's highest image quality in terms of resolution, dynamic range, color fidelity and geometric accuracy.

Phase One has grown to become the leading provider of high-end imaging technology across many demanding business segments, such as space imaging, aerial mapping, industrial inspection, and heritage digitization, as well as serving the world's most demanding professional photographers.

Based in Copenhagen, Denmark, and with regional offices in New York, Denver, Cologne, Tel Aviv, Tokyo, Beijing, Shanghai, and Hong Kong, Phase One nurtures long-term relationships with customers, technology partners and its global network of distributors, often playing the role of digital imaging partner to customers with unique requirements. It is with this passion for service that Phase One continually exceeds expectations and drives the imaging industry forward.

IMAGING BEYOND IMAGINATION

Contact your Phase One representative regarding availability of Phase One products in your region.

© Phase One A/S 2023, all rights reserved.